

MATLAB Memory:

Variables
Functions

Variables:

Scalar
Vector
Matrix (vector)

```
>> A = 10;
>> B = zeros(1,A);
>> C = zeros(A,1);
>> D = zeros(A,A);
>> E = zeros(A,A,A);
>>
>> whos
  Name      Size                      Bytes  Class
  A            1x1                      8    double array
  B            1x10                     80   double array
  C            10x1                     80   double array
  D            10x10                    800  double array
  E            10x10x10                 8000 double array

Grand total is 1121 elements using 8968 bytes
```

```
>>
```

Output

```
>> A = zeros(1,10);
>> B = zeros(1,10)


B =

          0     0     0     0     0     0     0     0     0     0

>>
```

```
>> clear      % CLEAR VARIABLES
>> clear all % CLEAR VARIABLES AND FUNCTIONS
```

Using Functions



Arithmetical operations

```
>> A = 10;
>> B = zeros(1,A);
>> C = zeros(A,1);
>> D = zeros(A,A);
>> E = zeros(A,A,A);
>>
>>
>>
>> A1 = A + 5 + A*5 + A/5 + A^5 + sin(A);
>> % SCALAR OPERATIONS
>>
>> B1 = B + B*5 + B.*B + B./B + B.^5 + sin(B);
>> % VECTOR OPERATIONS
>>
>> C1 = C + B';
>> % TRANSPOSE
>>
>>
>>
```

Logics

```
sample.m
for ind = 1:10,
    T(ind)=ind;
    Blabla=1;
    Blabla=2;
end
```

Graphics

```
plotting.m
for ind=1:10,
    T(ind)=ind;
end

figure(1);
plot(T,sin(T));
```

Check:

```
plot /  
  
subplot  
xlabel  
ylabel  
  
hold on / hold off  
  
comet
```

Plot:

```
x=(0.1:0.1:10); % vector of 0.1->10 with step 0.1
```

<pre>sin(x)/x (red)</pre>
<pre>x^3 (blue)</pre>
<pre>x^2 (green)</pre>

on single plot;

Function:

```
phases.m  
function [a1 a2] = phases(x);  
  
a1 = sin(0.9*x);  
a2 = cos(1.1*x);
```

write pirveli.m that will:

1. `x=(0:0.1:10);`
2. `plot a1(x), a2(x) on single plot, figure(1);`
3. `plot a1(a2), a2(a1) on subplot(1,2,1) and subplot(2,1,2) of figure(2);`
4. `figure(3): animation a1(a2) with comet.`